Material Safety Data Sheet



ITW Texwipe® Wipers pre-wetted with 6% IPA

1. Product and company identification

Product name : ITW Texwipe® Wipers pre-wetted with 6% IPA

Code : TX1048, TX8398, TX8488

Material uses : For use in Cleanroom Environments and Other for various cleaning and Cleanroom

Maintenance Operations.

Supplier/Manufacturer : ITW Texwipe

1210 South Park Drive Kernersville, NC 27284

Tel: 1-(336) 996-7046 (Toll Free: 1-(800) 839-9473)

Fax : 1-(336) 996-6563 Website : www.texwipe.com

MSDS authored by : KMK Regulatory Services Inc.

In case of emergency : CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

Emergency overview

Physical state : Pre-wetted wipers.

Color : Colorless.

Odor : Rubbing alcohol.
Signal word : WARNING!

Hazard statements : CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS

MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. COMBUSTIBLE. VAPOR

MAY CAUSE FLASH FIRE.

Precautionary measures: Keep away from heat, sparks and flame. Do not breathe vapor or mist. Avoid contact

with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly

closed and sealed until ready for use. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation: Irritating to respiratory system.

Ingestion : No known significant effects or critical hazards.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: central nervous

system (CNS).

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion: No specific data.

K~X

TX1048, TX8398, TX8488



2. Hazards identification

Skin

: Adverse symptoms may include the following: irritation

redness

redness

Eyes

: Adverse symptoms may include the following: pain or irritation watering

Medical conditions aggravated by overexposure : Repeated skin exposure can produce local skin destruction or dermatitis. Repeated exposure of the eyes to a low level of dust can produce eye irritation.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

| Name | CAS number | % |
|-------------|------------|---|
| Propan-2-ol | 67-63-0 | 6 |

Canada

| Name | CAS number | % |
|-------------|------------|---|
| Propan-2-ol | 67-63-0 | 6 |

| <u>Mexico</u> | | | | Classification | | | | |
|---------------|---------------|-----------|---|----------------|---|---|---|---------|
| Name | CAS number | UN number | % | IDLH | Н | F | R | Special |
| Propan-2-ol | 67-63-0 | UN1219 | 6 | 2000 ppm | 1 | 3 | 0 | |

Final product is comprised of solid cloth media that is saturated with the above components. Fill volume is controlled to ensure that no free liquid is present in the final product packaging.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

: Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention if symptoms occur.

Inhalation

: Move exposed person to fresh air. Get medical attention if symptoms occur.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Notes to physician

: No specific treatment. Treat symptomatically.

5. Fire-fighting measures

Flammability of the product

: Combustible

Extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable

Suitable

: Do not use water jet.

Hazardous decomposition products

: Decomposition products may include the following materials: carbon dioxide

Special protective equipment for fire-fighters

carbon monoxide
Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

K~X



6. Accidental release measures

Personal precautions

: Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Spill

: Place spilled material in an appropriate container for disposal.

7. Handling and storage

Handling

: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Wash thoroughly after handling.

Storage

: Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

United States

| Ingredient | Exposure limits | |
|-------------|--|--|
| Propan-2-ol | ACGIH TLV (United States, 2/2010). STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s). NIOSH REL (United States, 6/2009). STEL: 1225 mg/m³ 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 980 mg/m³ 10 hour(s). TWA: 400 ppm 10 hour(s). OSHA PEL (United States, 6/2010). TWA: 980 mg/m³ 8 hour(s). TWA: 400 ppm 8 hour(s). | |

Canada

| Occupational exposure limits | | TWA (8 hours) | | STEL (15 mins) | | Ceiling | | | | | |
|------------------------------|---|---------------------------------|---------------------------|------------------|---------------------------------|----------------------------|------------------|------------------|------------------|-------|-----------|
| Ingredient | List name | ppm | mg/m³ | Other | ppm | mg/m³ | Other | ppm | mg/m³ | Other | Notations |
| | US ACGIH 2/2010 AB 4/2009 BC 9/2010 ON 7/2010 QC 6/2008 | 200 200 200 200 400 | - 492 - - 983 | - - - - | 400 400 400 400 500 | - 984 - - 1230 | - - - - | - - - - | - - - - | - | |

Mexico

Occupational exposure limits

| Ingredient | Exposure limits |
|-------------|---|
| Propan-2-ol | NOM-010-STPS (Mexico, 9/2000). LMPE-CT: 1225 mg/m³ 15 minute(s). LMPE-CT: 500 ppm 15 minute(s). LMPE-PPT: 980 mg/m³ 8 hour(s). LMPE-PPT: 400 ppm 8 hour(s). |

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use explosion-proof ventilation equipment.



8. Exposure controls/personal protection

Hygiene measures

: Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Respiratory

: Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure an MSHA/NIOSH-approved respirator or equivalent is used.

Hands

: Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).

Eyes

: Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Lab coat.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state

: Pre-wetted wipers.

Flash point

: Closed cup: 46°C (114.8°F) [Tagliabue.]

Color : Colorless.

Odor

: Rubbing alcohol.

VOC content

: 7.8% (w/w), 8% (w/w), 6.8% (w/w)

10. Stability and reactivity

Chemical stability

Conditions to avoid

: The product is stable.

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials **Hazardous decomposition** products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Reactive or incompatible with the following materials: oxidizing materials.

11. Toxicological information

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--------------------------|---------|---------------------------|----------|
| Propan-2-ol | LD50 Dermal LD50 Oral | | 12800 mg/kg 5000 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|------------------------|---------|-------|----------|-------------|
| Propan-2-ol | Eyes - Severe irritant | Rabbit | - | - | - |
| | Skin - Mild irritant | Rabbit | - | - | - |

Carcinogenicity

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|-------|
| Propan-2-ol | A4 | 3 | - | - | - | None. |



11. Toxicological information

IDLH : Not available.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|---------------------------------------|----------|
| Propan-2-ol | Acute LC50 1400000 to 1950000 ug/L Marine water | Crustaceans - Crangon crangon | 48 hours |
| | Acute LC50 >1400000 ug/L | Fish - Gambusia affinis - 20 to 30 mm | 96 hours |

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

International transport regulations

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|--------------------------|-----------|--|---------|-----|-------|-----------------------------|
| DOT Classification | - | ORM-D | - | - | | - |
| TDG Classification | UN3175 | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol) | 4.1 | II | | Remarks Limited quantity |
| Mexico Classification | UN3175 | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol) | 4.1 | II | | Remarks Limited quantity |
| IMDG Class | UN3175 | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol) | 4.1 | II | | Remarks Limited quantity |
| IATA-DGR Class | UN3175 | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol) | 4.1 | II | | Remarks Limited quantity |

PG*: Packing group Exemption to the above classification may apply.

AERG: 133



15. Regulatory information

United States

HCS Classification : Irritating material

Target organ effects

U.S. Federal regulations : TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Propan-2-ol

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Propan-2-ol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health

hazard

Clean Air Act Section

112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 313

| | Product name | CAS number | Concentration |
|---------------------------------|--------------|------------|---------------|
| Form R - Reporting requirements | Propan-2-ol | 67-63-0 | 6 |
| Supplier notification | Propan-2-ol | 67-63-0 | 6 |

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Propan-2-ol

New York: None of the components are listed.

New Jersey: The following components are listed: Propan-2-olPennsylvania: The following components are listed: Propan-2-ol

California Prop. 65

No products were found.

Canada

WHMIS (Canada) : Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Isopropyl alcohol

CEPA Toxic substances : None of the components are listed.

Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification :



15. Regulatory information



International regulations

International lists

: Australia inventory (AICS): All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. Japan inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

16. Other information

Label requirements

: CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. COMBUSTIBLE. VAPOR MAY CAUSE FLASH FIRE.

Hazardous Material Information System (U.S.A.)

: Health: 1 * Flammability: 2 Physical hazards: 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

: Health: 1 Flammability: 2 Instability: 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Canada

WHMIS (Canada)



History

Date of issue : 02/28/2011

Date of previous issue : 03/15/2010

Version : 5

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

